

32" Digital Signage Monitor

(Industry Grade Metal Cabinet Design)

(TEL-32MRDS)

Main Function:

- Professional Design for Long Time Operation.
- High Resolution Full HD (1920 x 1080)
- Professional Metal Cabinet Design
- 7 International Languages OSD
- Power Failure Auto Recovery
- Anti Burn-in function
- HDMI/DVI/VGA Input
- Remote Controller
- Support RS-232
- Stand (optional)
- Speaker



(Stand optional)

Model	TEL-32MRDS
System	
Panel Size	32" LED
Panel Type	LED Backlight
Resolution	1920 x 1080
Pixel Pitch (H x V)	0.3637 x 0.3637
Contrast Ratio	3000:1
Luminance	350 cd/m ²
Aspect Ratio	16:9
Response Time	Grey to Grey = 6.5ms
View Angel	U/P: 85/85 , L/R: 85/85
Video Signal	Analog RGB Signal, Composite signal 0.6~1Vpp/75 ohm, Y:1Vp-p, C:0.3Vp-p
Video Color System	NTSC/PAL auto detection switch
Scan Frequency	H:31K~81KHz, V:56~75Hz
Operation Interfaces	
Front Panel Controls	Power,Source/Exit,+/- ,Menu/Enter
Indicators	LED
OSD Control	Yes
OSD Language	English, French, Germany, Spanish, Tranditional Chinese,Simplified Chinese, Japanese (7)
Input / Output Connector	
Input Connector	D-Sub (VGA) x 1 HDMI x 1 DVI x 1 RCA Audio (R/L) x 1 (Optional) RS-232 x 1 (Optional) Power Input (DC 24V) x 1 DC 5V Power Output x 1 DC 12V Power Output x 1 USB 5V Power Output x 1
Mechanical & Electrical Design	
Power Saving	No enter Saving mode when no singal, auto ON when singal resumes
VESA Mounting	200 x 200 mm & 300 x 200 mm
Front Bezel Material	Metal
Back Cabinet Material	Metal
Stand Material	Metal
Audio Power Output	5W x 2
Power	DC 24V
Power Consumption	100W(Max)
Working Temperature	5~+40 °C
Working Humidity	20% ~ 85%RH
Unit Dimension(WxHxD)	734 x 525 x 260 mm
Packing Dimension(WxHxD)	865 x 615 x 205 mm
Net Weight	13.0 Kg
Gross Weight	15.8 Kg
Regulatory	CE,FCC,RoHS
Color	Black
Accessory	
Power Cable	1
Power Adaptor	Input: AC 100~240V, 50/60Hz ; Output :DC 24V, 4.16A
D-Sub VGA Cable	1
3.5mm Audio Cable	1
User Manual (CD)	1
ID Remote Controller	1
Stand	Optional
Adaptor Holder	Optional