

42" Digital Signage Monitor

(Industry Grade Metal Cabinet Design)

(TEL-42MRDS)

Main Function:

- Professional Design for Long Time Operation.
- High Resolution Full HD (1920 x 1080)
- Professional Metal Cabinet Design
- 7 International Languages OSD
- Power Failure Auto Recovery
- Anti Burn-in function
- HDMI/DVI/VGA Input
- Remote Controller
- Support RS-232
- Stand (optional)
- Speaker



(Stand optional)

Model	TEL-42MRDS
System	
Panel Size	42" LCD (LED Backlight)
Resolution	1920 x 1080
Pixel Pitch (H x V)	0.4845(H) x 0.4845(V) mm
Contrast Ratio	4000:1
Luminance	500 cd/m2
Aspect Ratio	16:9
Response Time	Grey to Grey = 8 ms
View Angel	U/P: 89/89 , L/R: 89/89
Video Signal	Analog RGB Signal, Composite signal 0.6~1Vpp/75 ohm, Y:1Vp-p, C:0.3Vp-p
Video Color System	NTSC/PAL auto detection switch
Scan Frequency	H:31K~81KHz, V:56~75Hz
Operation Interfaces	
Front Panel Controls	Source/Exit, Power ,+ , - , Menu/Enter
Indicators	LED
OSD Control	Yes
OSD Language	English, French, Germany, Spanish, Tranditional Chinese, Simplified Chinese, Japanese (7)
Input / Output Connector	
Input Connector	HDMI x 1 DVI x 1 VGA x 1 PC 3.5mm Audio x 1 RS-232 x 1 (Optional) Power Input (AC 100-240V, 50/60Hz) x 1 DC 5/12V External Power Output x 1 (Optional)
Mechanical & Electrical Design	
Power Failure Auto Recovery	Yes
Anti Burn-in	Yes
Power Saving	Customized (No enter Saving mode when no singal, auto ON when singal resumes)
VESA Mounting	200 x 200 mm, 300 x 200 mm
Front Bezel Material	Metal
Back Cabinet Material	Metal
Stand Material	Metal
Audio Power Output	5W x 2 (Optional)
Power	AC 100~240V, 50/60Hz
Power Consumption	120W (Max)
Working Temperature	5~+40 °C
Working Humidity	20% ~ 85%RH
Unit Dimension(WxHxD)	963 x 555 x 85 mm
Packing Dimension(WxHxD)	1093 x 710 x 205 mm
Net Weight	20.0 Kg
Gross Weight	23.5 Kg
Regulatory	CE, FCC, RoHS
Color	Black
Accessory	
Stand	Optional
Power Cable	1
D-Sub VGA Cable	1
Remote Controller	1
User Manual (CD)	1