

VT79



Key pad option

Mode	Teleview part no.	Description
1	CPCB-VT79K1--	5 Key+LED , 5mm
2	CPCB-VT79K3--	5Key+LED , 5mm +IR

Features

- Support OSD adjustment for LCD display

Board Overall View

- Key SW x5
- Dual color LED , Green and Yellow .
- IR receiver for remote control function (Optional).

Connectors Description

CN1 : Input connector (2.0mm , 11 Pin, DIP)--with IR function

Input connector (2.0mm , 8 Pin, DIP)---without IR function

Pin	Function	Note
1	SEL+(RIGHT)	Increase the value
2	SEL-(LEFT)	Decrease the value
3	AUTO/EXIT	Menu Exit or VGA Auto adjusts
4	MENU	Enter the main menu
5	POWER	Power ON/OFF
6	LED-G	Green LED (Power ON)
7	LED-R	Red LED (Power saving)
8	GND	Ground
9	5V	+5Vdc
10	IR data	Interrupt input
11	GND	Ground

Key SW Height

Standard : 5.0 mm above the PCB surface , PCB thickness 1.6mm

Options : 7.0 mm , 9.5 mm , 13 mm .

LED Height

6.5 mm above the PCB surface , PCB thickness 1.6mm

IR receiver Height

5.2 mm above the PCB surface , PCB thickness 1.6mm

CN1 Height (Reverse side)

5.0 mm above the PCB surface , PCB thickness 1.6mm

Board Dimension :128mm x 12 mm

Screw holes*2:3mm

